## **Basic Facts**

- Architects: Holabird & Roche
- Consulting engineer: Henry J. Burt
- Construction company: John Griffiths & Son
- Construction supervisor: Frederick J. Thielbar
- Original site dimensions: 132 feet (Clark Street frontage) by 80 feet (Washington Street frontage)
- Additions to site: 21 to 27 Clark Street (50 feet by 80 feet) purchased from estate of David A. Kohn and leasehold from Harry C. Moir
- Temple dimensions: 182 feet (Clark Street) by 80 feet (Washington Street)
- **Construction material**: Indiana limestone; Bedford stone (lobby and vestibule); Batesville and Belgian Black Marble (entry floors)
- Foundation: concrete piles (caissons) resting on bedrock (38 on bedrock, 5 on hardpan)
- Caisson average depth: 115 feet
- Caisson diameter: from five feet to eight feet, four inches
- Structural framework: steel with terra cotta tile arch floors and roof
- Exterior walls: Bedford limestone backed with brick
- Tower: some steel framing, but mostly a gravity structure of masonry covered with Bedford stone
- **Spire**: light steel framework covered with reinforced concrete
- Number of stories: 22 (highest floor available for rental: 21)
- Building height: 260 feet
- Tower height: 140 feet
- Spire height: 156 feet
- **Cross**: 12 feet high, 6 feet wide, made of bronze, plated with copper, covered in gold leaf, and weighs 250 pounds
- Sanctuary walls: Heavily panelled in quarter sawed red (some sources say white) oak
- Sanctuary capacity (as originally designed): 800 on first floor, 400 in balcony (sources vary)
- Construction loan underwriter: Northwestern Mutual Life Insurance Company (Milwaukee, WI)
- Total value of building and property when opened: \$5,000,000